

## **LKH 70**

The LKH 70 data logger can be configured without software using a configurator PDF file, and at the end of the programming it issues an automatic PDF report indicating the alarms and a summary of the recorded data.

Ideal for humidity & temperature registration in warehouses and during transport. Allows you to change the interval and use different delayed activation modes. For the more advanced, downloadable software is available to configure the equipment, view the data table and custom graphics, export to Excel for analysis and calculations.



APPLICATIONS
HVAC
Storage and transport
Maintenance and Service
All kind of Industries

**HIGHLIGHTS** 

Operating PDF software available
Memory capacity of 50,000 points
2 programmable alarm thresholds
Software free downloadable
1 line LCD display

## **General Information**

PDF configurator:

Allows the configuration of the logger and the download of the automatic report in PDF

Software (downloadable):

It allows the configuration of the logger and the downloading of data to view in a table or graph.

It can be exported to EXCEL format.

**Technical Data** 

-20 ...+70°C 0 ... 100%RH Measuring range

± 0.4°C

from 0 to 50°C ± 2.5%RH Accuracy

± 0.8°C (5...95%RH, 15°C to 25°C)

below 0°C

Resolution 0.1°C 0.1%RH

Temp: NTC Humidity: Capacitive Internal sensor:

°C/F %RH Displayed units

Communication USB A male connector

50 000 Number of points recording

Interval recording From 1 minute to 24 hours

Alarm thresholds 2 limits

-20 ...+70°C Temperature of use Storage temperature -40 ...+85°C

IP20 Protection Weight 53g

Dimmensions 100x42,5x15,9mm Power supply CR2450 button cell

Autonomy 500 days, with interval 15 minutes at 25°C

PDF Configurator Use only with Adobe software Acrobat Reader 9 or higher

## Scope of delivery

Basic Humidity & Temperature Datalogger LKH 70

PDF configurator, Calibration protocol and Instruction manual included in the datalogger

Software (downloadable): Configuration and data management, including data transfer to EXCEL



LCD display



USB connection Waterproof closure



Battery cover

Battery closure indicator